



Photo Above: C0007-A Circular Bubble Level, 2.75" dia.

Description

Also referred to as a "bulls-eye" level, the C000X Series of Circular Bubble Levels provide accurate measurement of level in a rugged machined Aluminum housing (Anodized black). Several sizes available to fit any space requirement.

Manufactured to exacting specifications, the accuracy is guaranteed and maintained through the use of precision ground glass and machined Aluminum. Rigorous testing completed to assure high performance over long-term all weather conditions, exceeding Salt Fog survivability per ASTM B117.

Each instrument is filled with a special damping fluid that controls the movement of the bubble. The background is a metallic silver finish, providing the best contrast for viewing bubble position. Each concentric circle is enamelled to the surface eliminating distortion seen if markings were printed below the liquid and bubble.

These precision circular vials have three mounting holes for installation convenience and calibration. Since most mounting surfaces may vary, for exact zero calibration the C000X-A models all come with Polyurethane bumpers and mounting hardware.

Features

- ALL-Weather Machined Aluminum Housing
- Precision Ground Glass - No Discoloration or Cracking over time
- Permanently Fused Ceramic Markings
- Metallic Silver Finish for High Contrast Visibility of Bubble Position
- Temperature Range -40°C to +75°C/+85°C

Applications

- Quick and Accurate Visual Reference
- Leveling, Balancing and Preventing Tip-over
- Machining or Anywhere Precise Leveling Required

Equipment Types

- Aerial lift trucks, Bucket/utility trucks, Cranes, Construction Equipment, Conveyor and Material Handling Equipment, Emergency and Fire Aerial Ladder trucks, Government and Military Vehicles, Recreational Vehicles (RV), and Trailers

Rieker Accurate, Rieker Rugged.

34 MOUNT PLEASANT ROAD • ASTON • PA • 19014 • USA

610-500-2000

fax: 610-500-2002

info@riekerinc.com

www.riekerinc.com

GENERAL TECHNICAL DATA					
Environmental Testing	Salt-Fog per ASTM B117				
Housing Material	Machined Aluminum, Anodized Black, background metallic silver				
Glass Construction	Precision Ground Glass, Enameled (permanent) Ceramic Markings				
Operating Temperature	-40°C to +85°C (-40° F to +185° F); C0003 -40°C to +75°C (-40° F to +167° F)				
MECHANICAL SPECIFICATIONS					
Sensitivity per 0.1"	Concentric Rings	Cross Hair	Outside Dia. (inches)	Height (inches)	P/N #
45 Minutes	1	--	1.25	0.44	C0004-A
20 Minutes	1	--	1.44	0.50	C0005-A
10 Minutes	1	--	2.00	0.68	C0006-A
10 Minutes	1	--	2.75	0.69	C0007-A
10 Minutes	4	yes	3.15	0.49	C0003-A
BUBBLE LEVEL ORDERING SPECIFICATIONS					
Part Number #	Description				Hardware P/N#
C0004-A	1.25" Circular Level, 1 Ring, Mounting Bumper & Hardware				E-309
C0005-A	1.44" Circular Level, 1 Ring, Mounting Bumper & Hardware				E-309
C0006-A	2.00" Circular Level, 1 Ring, Mounting Bumpers & Hardware				E-308
C0007-A	2.75" Circular Level, 1 Ring, Mounting Bumpers & Hardware				E-318
C0003-A	3.15" Circular Level, Cross Hair Rings at 0°, 1°, 3°, 5° rings, Bumpers & Hardware				E-324

Contact us today for a quote. OEMs welcome, quantity pricing available.



Photo 1: C000X-A Series



Photo 2: C0003-A, 3.15" dia, 4 Concentric Rings

Rieker Accurate, Rieker Rugged.

34 MOUNT PLEASANT ROAD • ASTON • PA • 19014 • USA

610-500-2000

fax: 610-500-2002

info@riekerinc.com

www.riekerinc.com